

Claim Amendments

1. (currently amended) An apparatus, comprising:

a computer component that receives one or more images of one or more packaging materials from one or more imaging components;

wherein the computer component employs one or more irradiation components to emit one or more radiation wavelengths to the one or more packaging materials, wherein the computer component employs the one or more imaging devices to create the one or more images;

wherein the one or more packaging materials allow a transmittance of one or more of the one or more radiation wavelengths;

wherein the computer component employs one or more of the one or more irradiation components to emit the one or more of the one or more radiation wavelengths for the transmittance through one or more of the one or more packaging materials, wherein the one or more of the one or more radiation wavelengths reflect off a carrier of the one or more of the one or more packaging materials to the one or more imaging devices;

wherein the computer component employs an analysis of the one or more images to make a determination of a package integrity of the one or more packaging materials.

2. (original) The apparatus of claim 1, wherein the computer component employs one or more algorithms to conduct the analysis of one or more of the one or more images to make the determination of the package integrity of the one or more packaging materials.

3. (original) The apparatus of claim 1, wherein the one or more packaging materials comprise one or more seal regions, wherein the package integrity comprises a seal region integrity, wherein the computer component employs the analysis of the one or more images to make the determination of the seal region integrity of the one or more seal regions.

4-5. (canceled)

6. (original) The apparatus of claim 4, wherein the one or more packaging materials allow a transmittance of one or more of the one or more radiation wavelengths;

wherein the computer component employs one or more of the one or more irradiation components to emit the one or more of the one or more radiation wavelengths for a transmittance through one or more of the one or more packaging materials; wherein the one or more of the one or more radiation wavelengths transmit directly through the one or more of the one or more packaging materials to the one or more imaging devices.

7. (original) The apparatus of claim 4, wherein one or more of the one or more packaging materials allow a reflection of the one or more radiation wavelengths;

wherein the computer component employs one or more of the one or more irradiation components to emit the one or more radiation wavelengths at an incident angle to the one or more of the one or more packaging materials;

wherein upon the reflection of one or more of the one or more radiation wavelengths at an angle equal to the incident angle, the computer component employs the analysis to identify one or more dark regions in the one or more images, wherein the one or more dark regions indicate the package integrity to the computer component.

4

NGC-145 / 000312-040

8. (original) The apparatus of claim 4, wherein one or more of the one or more packaging materials allow a reflection of the one or more radiation wavelengths;

wherein the computer component employs one or more of the one or more irradiation components to emit the one or more radiation wavelengths at a low incident angle to the one or more of the one or more packaging materials;

wherein upon the reflection of one or more of the one or more radiation wavelengths different from the low incident angle, the computer component employs the analysis to identify one or more bright regions in the one or more images, wherein the one or more bright regions indicate the package integrity to the computer component.

9. (original) The apparatus of claim 4, wherein the computer component employs the one or more irradiation components to emit one or more of the one or more radiation wavelengths through one or more optical components.

10. (currently amended) ~~The apparatus of claim 9.~~ An apparatus, comprising:
a computer component that receives one or more images of one or more packaging
materials from one or more imaging components;

wherein the computer component employs one or more irradiation components to emit
one or more radiation wavelengths to the one or more packaging materials, wherein the computer
component employs the one or more imaging devices to create the one or more images;

wherein the computer component employs the one or more irradiation components to
emit one or more of the one or more radiation wavelengths through one or more optical
components;

wherein the computer component employs an analysis of the one or more images to make
a determination of a package integrity of the one or more packaging materials;

wherein one or more of the one or more packaging materials comprise one or more
graphics, wherein the computer component employs one or more of the one or more imaging
devices to determine one or more absorption spectrums of the one or more graphics;

wherein the computer component employs the one or more of the one or more irradiation
components to emit the one or more of the one or more radiation wavelengths to the one or more
of the one or more packaging materials, wherein the computer component employs the one or
more optical components to filter out the one or more absorption spectrums from the one or more
of the one or more radiation wavelengths.

11. (original) The apparatus of claim 9, wherein the computer component employs the one or more of the one or more irradiation components and the one or more optical components to create the one or more of the one or more radiation wavelengths, wherein the one or more of the one or more radiation wavelengths contact one or more of the one or more packaging materials.

12. (currently amended) ~~The apparatus of claim 9,~~ An apparatus, comprising:
a computer component that receives one or more images of one or more packaging
materials from one or more imaging components;

wherein the computer component employs one or more irradiation components to emit
one or more radiation wavelengths to the one or more packaging materials, wherein the computer
component employs the one or more imaging devices to create the one or more images;

wherein the computer component employs the one or more irradiation components to
emit one or more of the one or more radiation wavelengths through one or more optical
components;

wherein the computer component employs an analysis of the one or more images to make
a determination of a package integrity of the one or more packaging materials;

wherein the one or more of the one or more irradiation components comprise one or more
fluorescing excitation sources, wherein the one or more optical components comprise a first
band-pass filters, wherein the first band-pass filter allows the one or more of the one or more
radiation wavelengths of the one or more fluorescing excitation sources to pass through to one or
more of the one or more packaging materials;

wherein one or more compounds within the one or more of the one or more packaging
materials react to the one or more of the one or more radiation wavelengths of the one or more
fluorescing excitation sources, wherein the one or more compounds emit one or more fluorescing
wavelengths;

wherein the one or more optical components comprise a second band-pass filters,
wherein the second band-pass filter allows the one or more fluorescing wavelengths to pass
through to the one or more imaging devices.

13. (original) The apparatus of claim 1, wherein the computer component employs one or more material handling components to cause one or more deformations in one or more of the one or more packaging materials;

wherein the computer component receives one or more images of the one or more deformations from the one or more imaging components;

wherein the computer component employs an analysis of the one or more deformations to make a determination of the package integrity of the one or more of the one or more packaging materials.

14. (original) The apparatus of claim 1, wherein the computer component receives the one or more images of the one or more packaging materials from the one or more imaging components to perform an automated inspection of the package integrity of the one or more packaging materials.

15. (currently amended) A method, comprising the steps of:

employing one or more irradiation components to emit one or more radiation wavelengths to one or more packaging materials, wherein the one or more packaging materials allow a transmittance of one or more of the one or more radiation wavelengths, wherein the one or more imaging devices create the one or more images of the one or more packaging materials;

receiving one or more images of the one or more packaging materials from one or more imaging components; and

employing one or more analysis algorithms on the one or more images to make a determination of a package integrity of the one or more packaging materials;

wherein the step of receiving the one or more images of the one or more packaging materials from the one or more imaging components comprises the steps of:

employing the one or more irradiation components to emit the one or more of the one or more radiation wavelengths for the transmittance through the one or more packaging materials;
and

receiving the one or more images from the one or more imaging devices upon a reflection of the one or more of the one or more radiation wavelengths off a carrier of the one or more packaging materials to the one or more imaging devices..

16. (canceled)

17. (original) The method of claim 15, wherein the one or more packaging materials allow a transmittance of one or more of the one or more radiation wavelengths, wherein the one or more imaging devices create the one or more images of the one or more packaging materials, wherein the step of receiving the one or more images of the one or more packaging materials from the one or more imaging components comprises the steps of:

employing the one or more irradiation components to emit the one or more of the one or more radiation wavelengths for the transmittance through the one or more packaging materials;
and

receiving the one or more images from the one or more imaging devices images upon the transmittance of the one or more of the one or more radiation wavelengths through the one or more packaging materials to the one or more imaging devices.

18. (original) The method of claim 15, wherein the one or more packaging materials allow a reflection of the one or more radiation wavelengths, wherein the step of employing the one or more analysis algorithms on the one or more images to make the determination of the package integrity of the one or more packaging materials comprises the steps of:

employing the one or more irradiation components to emit the one or more radiation wavelengths at an incident angle to the one or more packaging components;

receiving the one or more images from the one or more imaging devices upon the reflection of one or more of the one or more radiation wavelengths at an angle equal to the incident angle;

employing the one or more analysis algorithms to identify one or more dark regions of the one or more images; and

employing the one or more dark regions of the one or more images to make the determination of the package integrity to the computer component.

19. (original) The method of claim 15, wherein the one or more packaging materials allow a reflection of the one or more radiation wavelengths, wherein the step of employing the one or more analysis algorithms on the one or more images to make the determination of the package integrity of the one or more packaging materials comprises the steps of:

employing one or more of the one or more irradiation components to emit the one or more radiation wavelengths at a low incident angle to the one or more packaging components;

receiving the one or more images from the one or more imaging devices upon the reflection of one or more of the one or more radiation wavelengths at an angle different from the incident angle; and

employing the one or more analysis algorithms to identify one or more bright regions of the one or more images;

employing the one or more bright regions of the one or more images to make the determination of the package integrity to the computer component.

20. (currently amended) ~~The method of claim 15, A method, comprising the steps~~
of:

employing one or more irradiation components to emit one or more radiation
wavelengths to one or more packaging materials, wherein the one or more packaging materials
comprise one or more graphics;

receiving one or more images of the one or more packaging materials from one or more
imaging components; and

employing one or more analysis algorithms on the one or more images to make a
determination of a package integrity of the one or more packaging materials;

~~wherein the one or more packaging materials comprise one or more graphics, wherein the~~
step of employing the one or more irradiation components to emit the one or more radiation
wavelengths to the one or more packaging materials comprises the steps of:

employing the one or more imaging devices to determine one or more absorption
spectrums of the one or more graphics; and

employing the one or more irradiation components to emit one or more of the one or
more radiation wavelengths through one or more optical components, wherein the one or more
optical components filter out the one or more absorption spectrums from the one or more of the
one or more radiation wavelengths.

21. (currently amended) ~~The method of claim 15, A method, comprising the steps~~
of:

employing one or more irradiation components to emit one or more radiation
wavelengths to one or more packaging materials, wherein the one or more irradiation
components comprise one or more fluorescing excitation sources;

receiving one or more images of the one or more packaging materials from one or more
imaging components; and

employing one or more analysis algorithms on the one or more images to make a
determination of a package integrity of the one or more packaging materials;

~~wherein the one or more irradiation components comprise one or more fluorescing~~
~~excitation sources;~~

wherein the step of employing the one or more irradiation components to emit the one or
more radiation wavelengths to the one or more packaging materials comprises the steps of:

employing a first optical component to allow a transmittance of one or more of the one or
more radiation wavelengths from the one or more fluorescing excitation sources through the one
or more packaging materials; and

employing a second optical component to allow one or more fluorescing wavelengths
emitted by the one or more packaging materials to pass through to the one or more imaging
devices.

22. (currently amended) An article, comprising:

one or more computer-readable signal-bearing media;

means in the one or more media for employing one or more irradiation components to emit one or more radiation wavelengths to one or more packaging materials, wherein the one or more packaging materials comprise one or more graphics;

means in the one or more media for receiving one or more images of the one or more packaging materials from one or more imaging components; and

means in the one or more media for employing one or more analysis algorithms on the one or more images to make a determination of a package integrity of the one or more packaging materials;

wherein the means in the one or more media for employing the one or more irradiation components to emit the one or more radiation wavelengths to the one or more packaging materials comprises:

means in the one or more media for employing the one or more imaging devices to determine one or more absorption spectrums of the one or more graphics; and

means in the one or more media for employing the one or more irradiation components to emit one or more of the one or more radiation wavelengths through one or more optical components, wherein the one or more optical components filter out the one or more absorption spectrums from the one or more of the one or more radiation wavelengths.